



STRATUS

With the best price-to-performance ratio in its class, Celerway STRATUS is the most advanced mobile communications solution available for rock-solid connectivity in a vast number of deployment scenarios.

| | |
|-------------------------------------|---|
| Maximum load balancing capacity | 950 Mbps |
| Phantom VPN encryption | 180 Mbps |
| IPSec VPN encryption | 60 Mbps |
| Maximum number of simultaneous WANs | 8 |
| Dimensions w x h x d | 210 mm x 43 mm x 145 mm |
| Weight | 1.05 kg |
| Operating temperature | -20 °C to 60 °C |
| Humidity | 5% to 85% |
| Power supply | 9-36V DC |
| Power consumption | 8-40W depending on use |
| Integrated cellular | 1 x CAT12 or 2 x CAT12 depending on model |
| Region | Global |
| SIM card slot | 2 x full size or 4 x full size (dual SIM for each modem) depending on model |
| eSIM support | eUICC with 2FF/3FF/4FF |
| Ethernet (WAN and/or LAN) | 5 x 10/100/1000 Mbps RJ-45 |
| Wi-Fi (WAN and/or LAN) | 2.4GHz + 5GHz simultaneous dual-band or 2.4GHz + 5GHz simultaneous dual-band + 2.4/5GHz WiFi depending on model |
| USB | 1 x USB 3.0 |
| Mini-PCIe | 1 x depending on model |
| M.2 | 1 x or 2 x depending on model |
| Antenna connectors cellular | 2 x SMA female or 4 x SMA female depending on model |
| Antenna connectors WiFi | 2x RP-SMA female or 4 x RP-SMA female depending on model |
| Antenna connectors GPS | 1 x SMA female |

PoE .at IN/OUT WAN/LAN configurable (1 x IN, 2 x OUT)

Rating E-Mark



TECHNICAL SPECIFICATION . Routers

STRATUS Double modem

3YP-CWY-5.2-E5L2W3

7090049150401

| | |
|---------------------------|---|
| Region | Global + Global |
| Dual SIM | Yes + Yes |
| Theoretical Upload Rate | 150 Mbps + 150 Mbps |
| Theoretical Download Rate | 600 Mbps + 600 Mbps |
| LTE-FDD | B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66 + B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66 |
| LTE-TDD | B38/39/B40/B41 + B38/39/B40/B41 |
| WCDMA | B1/B2/B3/B4/B5/B8/B19 + B1/B2/B3/B4/B5/B8/B19 |
| 2xCA | B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66; + B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66; |

3xCA DL interband 3CA:
B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:
B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:
B40+40+40; B41+41+41; B66+66+66;
+
DL interband 3CA:
B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:
B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:
B40+40+40; B41+41+41; B66+66+66;

WiFi Theoretical Data Rate 300Mbps + 867Mbps + 1.3Gbps

WiFi Protocol b/g/n + a/ac/b/g/n + a/ac/b/g/n

WiFi Frequency 2.4GHz + 5GHz + 2.4GHz/5GHz

Last modified 19-Jul-2021 19:12:44



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2022 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com



TECHNICAL SPECIFICATION . Routers

STRATUS Single modem

3YP-CWY-5.2-E5L1W2

7090049150418

| | |
|---------------------------|---|
| Region | Global |
| Dual SIM | Yes |
| Theoretical Upload Rate | 150 Mbps |
| Theoretical Download Rate | 600 Mbps |
| LTE-FDD | B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66 |
| LTE-TDD | B38/39/B40/B41 |
| WCDMA | B1/B2/B3/B4/B5/B8/B19 |
| 2xCA | B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66; |
| 3xCA | DL interband 3CA: B1+3+5/7/8/19/20/28; B1+7+20; B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30; B3+7+20; B3+7+28; B3+7+8; B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2; B66+12+30; B66+29+30; B66+5+30; B2+B14+B66; |
| | DL2 intraband plus interband 3CA: B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20; B3+3+28; B3+3+1; B4+4+5; B4+4+13; B7+7+28; B5+66+66; B13+66+66; B66+66+2; B39+B39+B41; B39+B41+B41; B14+B66+B66; |
| | DL3 intraband 3CA: B40+40+40; B41+41+41; B66+66+66; |

WiFi Theoretical Data Rate 300Mbps + 867Mbps

WiFi Protocol b/g/n + a/ac/b/g/n

WiFi Frequency 2.4GHz + 5GHz

Last modified 19-Jul-2021 19:12:44



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2022 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com



TECHNICAL SPECIFICATION . Routers

STRATUS WiFi

CWY-M5.2E5W3

7090049150623

WiFi Theoretical Data Rate 300Mbps + 867Mbps + 1.3Gbps

WiFi Protocol b/g/n + a/ac/b/g/n + a/ac/b/g/n

WiFi Frequency 2.4GHz + 5GHz + 2.4GHz/5GHz

Last modified 19-Jul-2021 19:12:45



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2022 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com